

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

1 Identification

- **Trade name:** UZIN Xtra Color
- **Application of the substance / the mixture** Colored grouting mortar
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Manufacturer:
 UZIN UTZ AG
 Dieselstrasse 3
 D-89079 Ulm
 Germany
 Tel.: +49 (0)731 4097-0
 Fax: +49 (0)731 4097-110
- **Supplier:**
 Uzin Utz North America, Inc.
 14509 E. 33rd. Place, Unit G
 Aurora, CO 80011
 Phone: +720-374-4810
 Toll-Free: +1 866-505-4810
 Fax: +1 720-374-2113
- **Information department:**
 Product safety department
 email: msds.info@uzin-utz.com
- **Emergency telephone number:**
 For Chemical Emergency Spill Leak Fire Exposure or Accident
 Call CHEMTREC Day or Night: DOMESTIC NORTH AMERICA 800-424-9300
 International, call +49 621 60 43 333

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements**
 The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05, GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labeling:**
 Portland cement

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: **UZIN Xtra Color**

(Contd. of page 1)

Quartz (crystalline silica)

Titanium dioxide

- **Hazard statements**

Causes skin irritation.

Causes serious eye damage.

May cause cancer. Route of exposure: Inhalation.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Precautionary statements**

Keep out of reach of children.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of soap and water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **NFPA ratings (scale 0 - 4)**



Health = 2

Flammability = 0

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2

Flammability = 0

Reactivity = 0

- **Other hazards**

NFPA Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.

NFPA is the National Fire Protection Association.

HMIS Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.

HMIS®, the Hazardous Materials Identification System, is a registered mark of the National Paint and Coatings Association (NPCA).

* Chronic health effect possible - inhalation of silica dust may cause lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust. See sections 3, 8 and 11.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Hazardous ingredients:**

CAS: 65997-15-1	Portland cement ☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315; STOT SE 3, H335	25-50%
CAS: 14808-60-7	Quartz (crystalline silica) ☠ Carc. 1A, H350; STOT RE 1, H372	1-<3%
CAS: 13463-67-7	Titanium dioxide ☠ Carc. 2, H351	1-<3%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: **UZIN Xtra Color**

(Contd. of page 2)

· **Additional information:**

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.
The amount of respirable cristalline silica is less than 0.1 %.
For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.

Call a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂ extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Wear dust mask.

Avoid formation of dust.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Pick up mechanically.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 14808-60-7	Quartz (crystalline silica)	0.075 mg/m ³
-----------------	-----------------------------	-------------------------

CAS: 13463-67-7	Titanium dioxide	30 mg/m ³
-----------------	------------------	----------------------

· **PAC-2:**

CAS: 14808-60-7	Quartz (crystalline silica)	33 mg/m ³
-----------------	-----------------------------	----------------------

CAS: 13463-67-7	Titanium dioxide	330 mg/m ³
-----------------	------------------	-----------------------

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: **UZIN Xtra Color**

(Contd. of page 3)

· **PAC-3:**

CAS: 14808-60-7	Quartz (crystalline silica)	200 mg/m ³
CAS: 13463-67-7	Titanium dioxide	2,000 mg/m ³

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Prevent formation of dust.

Wear suitable protective clothing, gloves and eye/face protection.

Avoid contact with the eyes and skin.

When mixing wear suitable NIOSH-approved dust respirator.

Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· **Information about protection against explosions and fires:** No special measures required.· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Keep receptacle tightly sealed.· **Information about storage in one common storage facility:** Store away from foodstuffs.· **Further information about storage conditions:**

Store in dry conditions.

Protect from humidity and water.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:**

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

· **Control parameters**· **Components with limit values that require monitoring at the workplace:****CAS: 65997-15-1 Portland cement**PEL Long-term value: 50 mppcf or 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 1* mg/m³

E; *as respirable fraction

CAS: 14808-60-7 Quartz (crystalline silica)PEL Long-term value: 0.05* mg/m³*resp. dust; 30mg/m³/%SiO₂+2REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³

*as respirable fraction

CAS: 13463-67-7 Titanium dioxidePEL Long-term value: 15* mg/m³

*total dust

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: **UZIN Xtra Color**

(Contd. of page 4)

REL See Pocket Guide App. A
 TLV Long-term value: 10 mg/m³

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Prevent formation of dust.
 Avoid contact with the eyes and skin.
 Wear suitable protective clothing, gloves and eye/face protection.
 Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.
- **Respiratory protection:**
 When mixing wear suitable NIOSH-approved dust respirator.
 Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).
- **Protection of hands:**



Use nitrile impregnated cotton-gloves

- **Material of gloves** Nitrile impregnated cotton-gloves
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Safety glasses

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Solid
Color:	Gray
Odor:	Light
Odor threshold:	Not determined.
- **pH-value at 20 °C (68 °F):** 11
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
- **Flash point:** Not applicable.
- **Flammability (solid, gaseous):** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: **UZIN Xtra Color**

(Contd. of page 5)

- | | |
|---|--|
| · Vapor pressure: | Not applicable. |
| · Density: | Not determined. |
| · Relative density | Not determined. |
| · Vapor density | Not applicable. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water: | Insoluble.
Sets with water. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Specific symptoms in biological assay:**
- **Primary route(s) of entry:** Inhalation, skin contact, eye contact, ingestion.
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:**
No sensitizing effects known.
Low in Chromate (< 2 ppm) acc. Regulation (EC) No 1907/2006 (REACH).
- **Subacute to chronic toxicity:**
The amount of respirable crystalline silica is less than 0.1 %.
Respirable crystalline silica (quartz) may cause a severe lung disease named silicosis. Symptoms of silicosis may be a shortness of breath, fever or cough. Silicosis is reported to increase the risk of carcinogenicity caused by continuous inhalation of respirable crystalline silica. Though the product itself contains less than 0.1% of respirable crystalline silica, respirable silica may be generated from working procedures such as grinding e.g. In general, inhalation of silica dust should be avoided. Therefore, for your own safety wear a suitable NIOSH-approved respirator in all occasions when handling of the product generates dust.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
CAS: 14808-60-7	Quartz (crystalline silica)
CAS: 13463-67-7	Titanium dioxide

I

2B

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: UZIN Xtra Color

(Contd. of page 6)

· **NTP (National Toxicology Program)**

CAS: 14808-60-7 Quartz (crystalline silica)

K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Carc. 1A

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Do not allow product to reach sewage system.
Mix product residues with water, allow to harden, then dispose of as construction waste.
- **Uncleaned packagings:**
- **Recommendation:** Empty paper packaging is recyclable.

14 Transport information

- | | |
|---|-----------------|
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · DOT, ADN, IMDG, IATA | |
| · Class | Void |
| · DOT, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport/Additional information: Not regulated as hazardous material according to the above specifications. | |
| · UN "Model Regulation": | Void |

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: UZIN Xtra Color

(Contd. of page 7)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)

· EPCRA Section 302 (Extremely Hazardous Substances):
--

None of the ingredient is listed.

· SARA Title III Section 313 (Toxic Release Inventory - TRI):
--

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- **Proposition 65 (California)**

- **Chemicals known to cause cancer:**

Crystalline silica (quartz) is classified as a substance known to the State of California to be a carcinogen.

Titanium dioxide (airborne, unbound particles of respirable size) is classified as a substance known to the State of California to be a carcinogen.

CAS: 14808-60-7	Quartz (crystalline silica)
-----------------	-----------------------------

CAS: 13463-67-7	Titanium dioxide
-----------------	------------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenicity categories**

· EPA (Environmental Protection Agency)
--

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 14808-60-7	Quartz (crystalline silica)	A2
-----------------	-----------------------------	----

CAS: 13463-67-7	Titanium dioxide	A4
-----------------	------------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 14808-60-7	Quartz (crystalline silica)
-----------------	-----------------------------

CAS: 13463-67-7	Titanium dioxide
-----------------	------------------

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms** GHS05, GHS07, GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Portland cement

Quartz (crystalline silica)

Titanium dioxide

- **Hazard statements**

Causes skin irritation.

Causes serious eye damage.

May cause cancer. Route of exposure: Inhalation.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Precautionary statements**

Keep out of reach of children.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2019

Version No. 3

Reviewed on 05/20/2019

Trade name: UZIN Xtra Color

(Contd. of page 8)

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of soap and water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:**

Jim Muggleton

Phone: +1 720-374-4810

Mobile: +1 720-413-5454

· **Date of preparation / last revision** 05/20/2019 / 2

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**